



6W | 420 lm | 3000K

LA-T38-6W-3000K-E26-MP-120V

IES/LDT photometry files
and product photography
available on request

PHYSICAL

Glass shape:	T38
Base:	E26
Materials:	Glass & nickel
Glass finish:	Matte White
Weight:	60g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54

ELECTRICAL

Power:	6W
Current:	0.05A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	70 lm/W
Lifetime:	30,000 hrs

ILLUMINATION

CCT:	3000K
Lumens:	420 lm
Incandescent equiv.:	37W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	70
TM30 - Rg	101
TM30 - Rf	94



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible
dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

Specification subject to change without
notice. Refer to our website for the most
recent product documentation. Tala
designs in the EU/UK are protected by
registered and or unregistered design rights